



FULL BODY HARNESSSES - H16

As per the H15 with side D rings and 2m lanyard

SAFERIGHT's basic full body harness is suitable for fall arrest and work positioning. Featuring fully adjustable leg, shoulder, chest and waist straps, the harness comes with a rear D attachment point for fall arrest and side Ds for work positioning. Ideal for occasional use.

Key Features

- Light weight and comfortable
- Rear attachment point
- Front attachment point
- Side D rings
- Yellow infill for easy identification
- Adjustable leg, shoulder, waist and chest strap
- Includes 2m lanyard

Materials & Construction

- 44mm T44 webbing
- Zinc plated fittings as standard
- Water/UV resistant webbing
- Weight 1.4 kg
- Minimum breaking load 15 kN

Options

- SAFERIGHT can customise any harness to suit specific requirements if required.

Testing & Quality Control

- 100% visual inspection
- Conforms to AS/NZS 1891.1 : 2007, License Number 1270
- SAFERIGHT is a Quality Endorsed Company to ISO 9001 : 2008

Measurement Table

SIZE	SHOULDER	CHEST	UPPER LEG
H16S	40 TO 60 CM	70 TO 110 CM	50 TO 110 CM
H16M	40 TO 70 CM	80 TO 130 CM	60 TO 120 CM
H16L	45 TO 70 CM	90 TO 150 CM	60 TO 130 CM
H16XL	45 TO 75 CM	90 TO 150 CM	60 TO 140 CM