



LANYARDS - RL

Lanyard - Retracting (Mini Block)

Retracting lanyards are ideal for many fall arrest applications where the anchor point is overhead or where there is a need to reduce fall distances. They act as an inertia device, similar to a seat belt, and lock immediately in the event of a fall, reducing both fall distance and forces. **NOTE: CAN BE USED IN 360 DEGREE WORKING RANGE.**

Key Features

- Locks up within 50 mm in the event of a free fall
- Built in fall indicator and shock absorber (not all models)
- Different style and material hooks available
- 2.5 m in length
- Triple action and double action hooks are available

Materials & Construction

- Steel triple action karabiner
- Double action alloy snap hook as standard
- 50 mm fluorescent yellow webbing
- Weight 1.2 kg

Testing & Quality Control

- 100% visual inspection
- Meets the requirements of AS/NZS 1891.3
- SAFERIGHT is a licensed manufacturer to AS/NZS 1891.1 : 2007, License Number 1270
- SAFERIGHT is a Quality Endorsed Company to ISO 9001 : 2008

Measurement Table

CODE	LENGTH	DESCRIPTION
RL1	2.5 m	50 mm webbing with triple action karabiners
RL2	2.5 m	50 mm webbing with triple action karabiner and triple action swivel karabiner
RL3	2.5 m	50 mm webbing with triple action karabiner and alloy snap hook
RLIKAR	2 m	25 mm webbing with triple action karabiner